

Insulating Tape in PE – White

Description: This is a polyethylene tape physically crosslinked white polyethylene foam, highly flexible with good thermal conductivity, with a self-adhesive surface and a disposable protective film. Its technical characteristics guarantee excellent flexibility. In addition, it is produced without the use of chlorofluorocarbons which are harmful to the environment. It is suitable as a finishing element on splices.

- **Thickness :** 3mm*
- **Width :** 50mm*
- **Roll length :** 10m
- **Color :** white
- **Thickness :** 3 mm (DIN EN 14304:2010-03)
- **DENSITY:** 30Kg/m³

- **APPLICATION TEMPERATURE:** 10° to 35°C
- **TEMP. operating temperature of the additive:** -20° to 75°C
- **TEMP. TEMP. OF APPLICATION OF THE MATERIAL:** -50° to +90°C

- **THERMAL CONDUCTIVITY:** 0.0372 W/ mK (at an average temperature of 40°C)
- **RESISTANCE FACTOR:** up to 2192μ (DIN 52615)
- **COMPRESSION RESISTANCE:** 190g/cm² (at 10%)
- **WATER ABSORPTION:** <2% of volume (after 28 days)
- **ADHESIVE:** synthetic
- **LINING:** LDPE

- **Quantity per box:** 24 rolls
- **Quantity per pallet:** 912 rolls

